



WESTLAKE

Project: \_\_\_\_\_

Model: \_\_\_\_\_ Series #: \_\_\_\_\_

Dealer: \_\_\_\_\_ Quantity#: \_\_\_\_\_

Delivery address: \_\_\_\_\_ Date: \_\_\_\_\_

# Bottom Mounted Series Reach in Solid door

Model#KR-23BG1(Refrigerator)



### Features

- Precision ventilated refrigeration system keeps food at safe temperature
- Electronic control system make it easy to adjust temperature set point and defrost frequency
- Self closing door with 90 degree stay open feature,locks and keys included
- Preinstalled heavy duty casters with brakes
- Removeable installation board makes it easy to access condenser coil for cleaning and service.
- Stainless steel exterior and interior, ensure longer life
- Full lighting vertical LED light,goes on when door open, goes off when door closed
- Anti-corrosion coated copper coil evaporator, and 100% copper coil condenser ensure 10 years life of westlake products
- 4 epoxy coated steel wire shelves, 155 lbs loading capacity each.
- R290 hydro carbon refrigerant that has zero(0) ozone depletion potential(ODP) & three(3) global warming potential(GWP)

### WARRANTY:

- 2 Years Parts and Labor
- 6 Years compressor (Additional 4 years parts only)
- westlake is responsible for components failure. but is not responsible for improper operation failure and artificial damage.



Parts & Labor



Compressor



Conforms to UL&NSF-7 Standards





# Bottom Mounted Series Reach in Solid door

Model#KR-23BG1(Refrigerator)

## TECHNICAL DATA

SKU	WKR-23BG
Model #	KR-23BG1
Temperature range	33~41°F
Refrigerant	R290
Max Ambient Temperature	100°F
Defrosting	automatic every 4 hours
Horsepower	1/4
Exterior Dimension	26 9/10"Wx30.7"Dx81 9/10"H
Interior Dimension	22 9/10"Wx24 1/5"Dx59 13/20"H
Gross Weight	288lbs
Net Weight	266lbs
Packing Dimension	29"Wx33"Dx84 3/5"H
Voltage/Phase/Hz	115V/1/60Hz
Amps	2.2
Plug Type	NEMA 5-15P
Electrical Cord Length	80"

## PLAN VIEW

