



WESTLAKE

Project: _____

Model: _____ Series #: _____

Dealer: _____ Quantity#: _____

Delivery address: _____ Date: _____

Bottom Mounted Series Reach in Glass door

Model#KR-82BG1(Refrigerator)

Features

- Precision ventilated refrigeration system keeps food at safe temperature
- Electronic control system make it easy to adjust temperature set point and defrost frequency
- Self closing door with 90 degree stay open feature,locks and keys included
- Preinstalled heavy duty casters with brakes
- Removeable installation board makes it easy to access condenser coil for cleaning and service.
- Stainless steel exterior and interior, ensure longer life
- Full lighting vertical LED light,goes on when door open, goes off when door closed
- Anti-corrosion coated copper coil evaporator, ensure 10 years life of westlake products
- 12 epoxy coated steel wire shelves, 155 lbs loading capacity each.
- R290 hydro carbon refrigerant that has zero(0) ozone depletion potential(ODP) & three(3) global warming potential(GWP)



WARRANTY:

- 2 Years Parts and Labor
- 6 Years compressor (Additional 4 years parts only)
- westlake is responsible for components failure. but is not responsible for improper operation failure and artificial damage.




Parts & Labor



Compressor



Conforms to UL&NSF-7 Standards







Bottom Mounted Series Reach in Glass door

Model#KR-82BG1(Refrigerator)

TECHNICAL DATA

SKU	WKR-82BG
Model #	KR-82BG1
Temperature range	33~40°F
Refrigerant	R290
Max Ambient Temperature	100°F
Defrosting	automatic every 4 hours
Horsepower	1/3P
Exterior Dimension	81.5*30.7*81.9
Interior Dimension	77.6*24.2*59.7
Gross Weight	613lbs
Net Weight	547lbs
Packing Dimension	83.7*33.5*85.8
Voltage/Phase/Hz	115V/1/60Hz
Amps	4.6A
Plug Type	NEMA 5-15P
Electrical Cord Length	80

PLAN VIEW



NEMA 5-15P